

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 July 2003 (31.07.2003)


PCT

(10) International Publication Number
WO 03/061509 A1

- (51) International Patent Classification⁷: A61C 5/10, B22F 3/08
- (21) International Application Number: PCT/SE02/02386
- (22) International Filing Date:
19 December 2002 (19.12.2002)
- (25) Filing Language: Swedish
- (26) Publication Language: English
- (30) Priority Data:
0104445-2 28 December 2001 (28.12.2001) SE
- (71) Applicant (for all designated States except US): NOBEL
BIOCARE AB (publ) [SE/SE]; Box 5190, S-402 26
Göteborg (SE).
- (72) Inventors; and
(75) Inventors/Applicants (for US only): BERGGREN, Ca-
rina [SE/SE]; Sidoljusvägen 6A, S-423 40 Torslanda (SE).
ERIKSSON, Mikael [SE/SE]; Gundefjällsgatan 45, S-431
51 Mölndal (SE).
- (74) Agent: OLSSON, Gunnar; Nobel Biocare AB, Box 5190,
S-402 26 Göteborg (SE).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: ARRANGEMENT, DEVICE, METHOD, PRODUCT AND USE IN CONNECTION WITH A BLANK MADE PREFERABLY OF TITANIUM POWDER



(57) **Abstract:** An arrangement for producing a blank made of metal powder, preferably titanium powder, intended for a dental crown or other product for the human body (spacer, dentine, implant, etc.) comprises at least one first apparatus for powder compression and at least one second apparatus with one or more elastic molds having at least one cavity for a punch (block) and the powder used in the initial stage. The first apparatus comprises a machine operating by impact compaction, and said mold or molds is/are arranged, when the cavity is filled with starting powder, to receive impacts effected by the impaction members in the machine and, as a function of the impact or impacts, to generate an isostatic action during the compression/compaction. The invention also relates to a device, method and use and permits a rapid production procedure while maintaining the current requirements in respect of precision and quality.